



Technical Data Sheet

DOWSIL™ Contractors Silicone Strip

FEATURES & BENEFITS

- Easy to install
- Recommended for use with DOWSIL™ 791 Silicone Weatherproofing Sealant
- Available in clear for ease of quality control and assurance of good sealant application
- Mechanical fastening is not required

COMPOSITION

- Preformed silicone elastomer extrusion

Preformed silicone seal for general building applications.

APPLICATIONS

DOWSIL™ Contractors Silicone Strip is a general purpose pre-formed silicone extrusion. It is available in 3, 4, 6, 9, and 12 inch widths and can be applied and adhered solely with silicone sealant.

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications.

Test*	Property	Unit	Result
As Supplied – Cured Rubber Extrusion			
ASTM D 412	Durometer Hardness, Shore A	points	43
ASTM D 412	Tensile Strength	psi (MPa)	> 800 (5.5)
ASTM D 412	Elongation	percent	> 400
ASTM D 624	Tear Strength, die B	ppi	50

*ASTM: American Society for Testing and Materials

HANDLING PRECAUTIONS

PRODUCT SAFETY PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT WWW.CONSUMER.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

PACKAGING INFORMATION

DOWSIL Contractors Silicone Strip is available in 100 foot rolls. Standard stocked sizes include widths of 3, 4, 6, 9 and 12 inches in clear.

LIMITATIONS

DOW Contractors Silicone Strip is not intended for use:

- With DOWSIL™ 790 Silicone Building Sealant as an adhesive
- With non-Dow sealants or acetoxycure silicone sealants as the bonding sealant
- In below-grade applications

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, www.consumer.dow.com or consult your local Dow representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

www.consumer.dow.com



®Trademark of The Dow Chemical Company

UNRESTRICTED – May be shared with anyone
®™Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
DOWSIL™ Contractors Silicone Strip
© 2017 The Dow Chemical Company. All rights reserved.

Form No. 63-6228-01 A